





## Reliable Polyurethane and Epoxy formulations for Electrical Components



Veeyor provides reliable formulations for power generation, management, and distribution components. Whatever may be requirement DTs, bushings, CTPTs, Instrument transformers, cables etc. Veeyor provides the widest range of chemical formulations suitable for low, medium or high voltage applications.



Consistent Quality



Timely Delivery



Competitive Pricing



Excellent Technical Support









## **Our range of systems - Power Transmission**

Product	Appearance	Mixed Viscocity cps@30°C	Mixed Density g/cc	Mixed Ratio	Hardness	TC W/mK	Curing Characteristics	Flammability Rating
VEEPU 300	Mahagony	10000- 12000	1.5-1.55	100:27:00	75-85 Shore D	0.7	RT Curing for 1 hr	NA
VEEFILL 323 FSP	Natural/ Mahagony	14000- 15000	1.6-1.7	100:100	80-90 Shore D	NA	HT curing @ 80-120°C for 3-4 hrs	NA
VEEFILL 4007	Red	50000- 55000	1.6-1.8	100:100	>80 Shore D	0.8-0.9	HT curing @ 120°C for 2-3 hrs	NA
VEEPOXY 401/H 105/ P107/A107	Transparent	3000- 4000	1.0-1.1	100:100:12:1	>80 Shore D	NA	HT curing @ 120°C for 1 hr	NA
VEEFILL 222H	RED	25000- 27000	1.7-1.75	100:100	70-80 Shore D	NA	HT curing @ 120°C for 2 hrs	NA
VEEFILL 315 F	RED	12000- 15000	1.6-1.7	100:05:00	>80 Shore D	NA	RT Curing	NA
VEEPU FR 262	Black	2000- 3000	1.4-1.5	100:25:00	60-70 Shore D	0.6	RT Curing for 2-3 hrs	Ul94 VO

<sup>\*</sup>Products are REACH and RoHS compliant

## **About us**

Veeyor Polymer is a leader in specialized Polyurethane, Epoxy Resin, and Silicone Sealing formulations. Our commitment to innovation and unwavering product quality drives us to create custom formulations precisely tailored to your unique requirements.

With decades of expertise and a dedicated team of researchers and scientists, we conduct rigorous research to enhance formulation attributes like appearance, chemical properties, viscosity, and other critical characteristics, ensuring the ideal chemistry for your applications.











Manufacturing **Plants** 



<sup>\*\*</sup> Setting time can be varied as per customer requirement

<sup>\*</sup>VEEPU: Polyurethane, VEEFILL: Epoxy, VEESIL: Silicone